

K o d i a k



P O P U L A R O P T I O N S

ATP Stoneguard

14" x 14" Non-Powered Roof Vent

12v Dome Light and Switch

D-Ring Tie Downs

32", 36" or 48" Side Door

Ramp Door

Light Package



No wheel well model shown.

T H E B E S T N A M E B E H I N D Y O U F O R T H E L O N G H A U L

Kodiak Specifications

Model		KD7X12DS2	KD7X12DT2	KD7X14DT2	KD7X16DT2	KD7X18DT2
Overall	Length	15'4"	15'4"	17'4"	19'4"	21'4"
	Width	93"	93"	93"	93"	93"
	Height	97"	97"	97"	97"	97"
Interior	Length	12'4"	12'4"	14'4"	16'4"	18'4"
	Width	81"	81"	81"	81"	81"
	Height	73"	73"	73"	73"	73"
Width Between Wheel Wells		66"	72 1/2"	72 1/2"	72 1/2"	72 1/2"
Platform Height		22"	22"	22"	22"	22"
Torflex EZ Lube Axles						
	Quantity	single	tandem	tandem	tandem	tandem
	Total Capacity	3500	7000	7000	7000	7000
	Type	drop	drop	drop	drop	drop
Brakes		2 wheel electric	4 wheel electric	4 wheel electric	4 wheel electric	4 wheel electric
Tire Size		ST205/R15 15"	ST205/R15 15"	ST205/R15 15"	ST205/R15 15"	ST205/R15 15"
Tire Load Range		C	C	C	C	C
Wheel Bolt Pattern		5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2	5 - 4 1/2
Hitch Ball Size		2"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Hitch Height to Top of Ball		19"	21"	21"	21"	21"
Hitch Weight		160	210	220	250	280
Curb Weight		1600	2060	2200	2540	2840
GVWR		3500	7000	7000	7000	7000
Payload Capacity (Avg.)		1900	4940	4800	4460	4160
Rear Doors	Std. Opt.	double ramp*	double ramp*	double ramp*	double ramp*	double ramp*
Camlocks		yes	yes	yes	yes	yes
Rear Opening	Dbl Door	73 1/2"	73 1/2"	73 1/2"	73 1/2"	73 1/2"
	Ramp Height	74 3/4"	74 3/4"	74 3/4"	74 3/4"	74 3/4"
	Height	67"	67"	67"	67"	67"
12V Male Connec.		7 way	7 way	7 way	7 way	7 way
ABS Front Cap		yes	yes	yes	yes	yes
Prefinished Aluminum Skin		.030	.030	.030	.030	.030
Interior Walls		3/8" ply	3/8" ply	3/8" ply	3/8" ply	3/8" ply
Floor		3/4" ply	3/4" ply	3/4" ply	3/4" ply	3/4" ply
Front Jack		yes	yes	yes	yes	yes
DOT Lighting/Dbl Bulb		yes	yes	yes	yes	yes
Safety Chains and Hooks		yes	yes	yes	yes	yes
Aluminum Fenders		yes	yes	yes	yes	yes
Breakaway Kit		yes	yes	yes	yes	yes
Floor Crossmembers = 24" OC		Wall Studs = 16" OC			Roof Bows = 24" OC	



Red



Indigo Blue



Black



Charcoal



Brandywine



White



Metallic Silver



Dove Gray



Forest Green



Champagne Beige

* Rear Ramp Door with Spring Assist

**Trailer Weights Will Vary When Optional Equipment is Added

Rev 302

Haulmark's Commitment to Quality

For over 20 years Haulmark has constructed the best-built trailers in America. We recognize and value the importance of strength, durability and quality and strive to give our customers nothing less.

Haulmark designs and construction reflect a tradition of total commitment to quality. Come see why Haulmark is "the best name behind you for the long haul."

800-348-7530 • www.haulmark.com

Indiana • Pennsylvania • Utah • Georgia • Arizona

All of the information printed was based on the latest product information available at the time of publication. Haulmark reserves the right to make changes at any time in prices, colors, materials, equipment, specifications and models and to discontinue models without notice or obligation. Photos may show optional equipment which is not a standard item on a particular unit. Please see your dealer for complete details about standard and optional equipment.

DEALER IMPRINT



Manufacturer of Steel Frame Trailers of Quality

© Copyright 1998 Haulmark Industries, Inc.